



3-2. Tube Pumps (Small Type) TR Series

	
TR-PU (Pump)	TR-CU (Quantity of injection controller)

APPLICATIONS

- Chemical liquid metering and subdividing
- Cosmetics factory
- Food factory
- Laboratory

SPECIFICATIONS

● Pump (MODEL : TR-PU)

Motor	AC Speed Controller 40W		
Speed Reduction Ratio	1/25		
Rotation Numbers of Roller	50Hz : 15~56 r /min 60Hz : 15~68 r /min		
Application Tube	3/8×5/8(t=1/8)	1/2×3/4(t=1/8)	5/8×7/8(t=1/8)
Standard Out-Put Capacity	50Hz : 80~1,100 ml/min 60Hz : 80~1,300 ml/min	50Hz : 130~1,800 ml/min 60Hz : 130~2,150 ml/min	50Hz : 180~2,500 ml/min 60Hz : 180~3,000 ml/min
Max. Discharge Pressure	0.1MPa		
Power Supply	AC100V 50/60Hz		
Operation System	ON / OFF Switch (Continuation)		
Injection Accuracy	±2% of the full scale		
Size	183W×265D×264H		
Weight	10 kg		
Tube	NORPRENE, PHARMED, SILICON etc.		

● Quantity of injection controller (MODEL : TR-CU)

Operation System	Button and Foot Switch
Interval Timer	Setting the cycle and time of ON/OFF with twin-timer
Cycle Setting Counter	0~999999 (pre-set)
Size	183W×180D×111H
Weight	1kg

Foot Switch is Option.

■ Reference

Elepon E.C.A.P. Corporation

Shin-Daibiru Bidg, 1-2-1,Dojimahama,Kita-ku,Osaka,530-0004,Japan

E-mail : sales@elepon.co.jp

URL : <http://www.elepon.co.jp>